

PVC Schedule 40 Bell End Pipe

Product Data Sheet PVC-40-BE-PIPE-623
Effective June 22, 2023
Supersedes Product Data Sheet
PVC-40-BE-PIPE-323

Possession of this product data sheet shall not be construed as an offer to sell the products listed.
"You can't beat the system" is a registered trademark of Charlotte Pipe and Foundry Company. ©2019-2023 Charlotte Pipe and Foundry Company.



>> PVC Schedule 40 Pipe - Bell End*

PVC SCHEDULE 40 (WHITE)			BELL END		PVC 1120		ASTM D 1785	
PART NO.	NOM. SIZE	UPC # 611942-	QTY. PER SKID	AVG. OD (IN.)	MIN. WALL (IN.)	MAX WORK PRESSURE AT 23° C OR 73° F	BELL DEPTH (IN.)	WT. PER 100 FT. (LBS.)
PVC 4005B**	½"x10'	04986	4500'	.840	.109	600 PSI	2.00	15.9
PVC 4005B**	½"x20'	03923	9000'	.840	.109	600 PSI	2.00	15.9
PVC 4007B**	¾"x10'	04987	3500'	1.050	.113	480 PSI	2.25	21.1
PVC 4007B**	¾"x20'	03926	7000'	1.050	.113	480 PSI	2.25	21.1
PVC 4010B**	1"x10'	04988	3000'	1.315	.133	450 PSI	2.50	31.3
PVC 4010B**	1"x20'	03929	6000'	1.315	.133	450 PSI	2.50	31.3
PVC 4012B§	1¼"x10'	04989	2000'	1.660	.140	370 PSI	2.75	42.4
PVC 4012B§	1¼"x20'	03930	4000'	1.660	.140	370 PSI	2.75	42.4
PVC 4015B§	1½"x10'	04990	1650'	1.900	.145	330 PSI	3.00	51.8
PVC 4015B§	1½"x20'	03931	3300'	1.900	.145	330 PSI	3.00	51.8
PVC 4020B†	2"x10'	04991	1110'	2.375	.154	280 PSI	4.00	69.5
PVC 4020B†	2"x20'	03932	2220'	2.375	.154	280 PSI	4.00	69.5
PVC 4025B‡	2½"x20'	04206	1460'	2.875	.203	300 PSI	4.00	110.0
PVC 7300B§	3"x10'	04853	1130'	3.500	.216	260 PSI	4.00	147.6
PVC 4030B†	3"x20'	03933	1000'	3.500	.216	260 PSI	4.00	144.2
PVC 7400B§	4"x10'	04835	670'	4.500	.237	220 PSI	4.00	212.3
PVC 9400B†	4"x20'	03964	1340'	4.500	.237	220 PSI	5.00	210.6
PVC 7600B§	6"x10'	04850	330'	6.625	.280	180 PSI	6.50	379.3
PVC 9600B†	6"x20'	03965	660'	6.625	.280	180 PSI	6.50	373.2
PVC 7800B†	8"x10'	09903	140'	8.625	.322	160 PSI	7.00	551.5
PVC 9800B†	8"x20'	03967	280'	8.625	.322	160 PSI	7.00	564.0
PVC 7910B†	10"x20'	03960	160'	10.750	.365	140 PSI	9.00	781.4
PVC 7912B†	12"x20'	03962	120'	12.750	.406	130 PSI	10.00	1033.2
PVC 7914B†	14"x20'	04863	60'	14.000	.437	130 PSI	10.00	1221.8
PVC 7916B†	16"x20'	04929	60'	16.000	.500	130 PSI	10.00	1594.5

* Bell dimensions meet either ASTM D 2672 or ASTM F 480, depending upon pipe diameter

** ASTM D 1785

§ Dual Marked ASTM D 1785 & ASTM D 2665

† Triple Marked ASTM D 1785 & ASTM D 2665 & ASTM F 480

‡ Dual Marked ASTM D 1785 & ASTM F 480


Note: PVC Schedule 40 Bell End pipe lengths for sizes 4", 6", and 8" are 20 feet, plus the bell [20 foot laying length]. The length for all other sizes of Schedule 40 Bell End pipe is 20 feet, including the bell.

You can't beat the system.®



WARNING

Testing with or use of compressed air or gas in ABS / CPVC / PVC / Cast Iron pipe or fittings can result in explosive failures and cause severe injury or death.



- NEVER test with or transport/store compressed air or gas in ABS / CPVC / PVC / Cast Iron pipe or fittings.
- NEVER test ABS / CPVC / PVC / Cast Iron pipe or fittings with compressed air or gas, or air over water boosters.
- ONLY use ABS / CPVC / PVC / Cast Iron pipe or fittings for water or approved chemicals.
- Refer to warnings on PPEA's website and ASTM D 1785.

TERMS AND CONDITIONS OF SALE

Terms and Conditions of Sale can be found at https://charlottepipe.com/terms_and_conditions.aspx

LIMITED WARRANTY

Charlotte Pipe and Foundry Company® (Charlotte Pipe®) Products are warranted to be free from manufacturing defects and to conform to currently applicable ASTM standards for a period of five (5) years from date of delivery. Buyer's remedy for breach of this warranty is limited to replacement of, or credit for, the defective product. This warranty excludes any expense for removal or reinstallation of any product and any other incidental, consequential, or punitive damages. **This limited warranty is the only warranty made by seller and is expressly in lieu of all other warranties, express and implied, including any warranties of merchantability and fitness for a particular purpose.** No statement, conduct or description by Charlotte Pipe or its representative, in addition to or beyond this Limited Warranty, shall constitute a warranty. This Limited Warranty may only be modified in writing signed by an officer of Charlotte Pipe.

This Limited Warranty will not apply if:

- 1) The Products are used for purposes other than their intended purpose as defined by local plumbing and building codes, and the applicable ASTM standard.
- 2) The Products are not installed in good and workmanlike manner consistent with normal industry standards; installed in compliance with the latest instructions published by Charlotte Pipe and good plumbing practices; and installed in conformance with all applicable plumbing, fire and building code requirements.
- 3) This limited warranty does not apply when the products of Charlotte Pipe are used with the products of other manufacturers that do not meet the applicable ASTM or CISPI standards or that are not marked in a manner to indicate the entity that manufactured them.
- 4) In hubless cast iron installations, this warranty will not apply if products are joined with unshielded hubless couplings. Charlotte Pipe requires that its hubless cast iron pipe and fittings be joined only with shielded hubless couplings manufactured in accordance with CISPI 310, ASTM C 1277 and certified by NSF® International or with Heavy Duty Couplings meeting ASTM C 1540.
- 5) The Products fail due to defects or deficiencies in design, engineering, or installation of the piping system of which they are a part.
- 6) The Products have been the subject of modification; misuse; misapplication; improper maintenance or repair; damage caused by the fault or negligence of anyone other than Charlotte Pipe; or any other act or event beyond the control of Charlotte Pipe.
- 7) The Products fail due to the freezing of water in the Products.
- 8) The Products fail due to contact with chemical agents, fire stopping materials, thread sealant, plasticized vinyl products, or other aggressive chemical agents that are not compatible.
- 9) Pipe outlets, sound attenuation systems or other devices are permanently attached to the surface of Charlotte® PVC, ABS or CPVC products with solvent cement or adhesive glue.

Charlotte Pipe products are manufactured to the applicable ASTM or CISPI standard. Charlotte Pipe and Foundry **cannot** accept responsibility for the performance, dimensional accuracy, or compatibility of pipe, fittings, gaskets, or couplings not manufactured or sold by Charlotte Pipe and Foundry.

This Limited Warranty will not apply unless written notice of a claim is mailed to Charlotte Pipe at the address below within 30 days of discovery of the allegedly defective product.

Any Charlotte Pipe products alleged to be defective **must** be made available to Charlotte Pipe at the following address for verification, inspection and determination of cause:

Charlotte Pipe and Foundry Company
Attention: Technical Services
2109 Randolph Road
Charlotte, North Carolina 28207

Purchaser must obtain a return materials authorization and instructions for return shipment to Charlotte Pipe of any product claimed defective or shipped in error.

Any Charlotte Pipe product **proved** to be defective in manufacture will be replaced F.O.B. point of original delivery, or credit will be issued, at the discretion of Charlotte Pipe.

5/19/23

Charlotte, Charlotte Pipe and "You can't beat the system" are registered trademarks of Charlotte Pipe and Foundry Company.