

# PVC Schedule 40 DWV and Pressure Pipe

Product Data Sheet PVC-40-PE-PIPE-124  
Effective January 1, 2024  
Supersedes Product Data Sheet  
PVC-40-PE-PIPE-322

Possession of this product data sheet shall not be construed as an offer to sell the products listed.  
"You can't beat the system" is a registered trademark of Charlotte Pipe and Foundry Company.  
©2019-2024 Charlotte Pipe and Foundry Company.



## >> PVC Schedule 40 Pipe - Plain End

PVC SCHEDULE 40 (WHITE)			PLAIN END		PVC 1120		ASTM D 1785	
PART NO.	NOM. SIZE	UPC # 611942-	QTY. PER SKID	AVG. OD (IN.)	MIN. WALL (IN.)	MAX WORK PRESSURE AT 23° C OR 73° F	WT. PER 100 FT. (LBS.)	
PVC 4005	½"x10'	06658	4500'	.840	.109	600 PSI	15.9	
PVC 4005	½"x20'	03922	9000'	.840	.109	600 PSI	15.9	
PVC 4007	¾"x10'	06661	3500'	1.050	.113	480 PSI	21.1	
PVC 4007	¾"x20'	03925	7000'	1.050	.113	480 PSI	21.1	
PVC 4010	1"x10'	06664	3000'	1.315	.133	450 PSI	31.3	
PVC 4010	1"x20'	03928	6000'	1.315	.133	450 PSI	31.3	
PVC 7100*	1¼"x10'	03945	2120'	1.660	.140	370 PSI	42.4	
PVC 7100*	1¼"x20'	03946	4240'	1.660	.140	370 PSI	42.4	
PVC 7112*	1½"x10'	03947	1650'	1.900	.145	330 PSI	51.8	
PVC 7112*	1½"x20'	03948	3300'	1.900	.145	330 PSI	51.8	
PVC 7200*	2"x10'	03949	1110'	2.375	.154	280 PSI	69.5	
PVC 7200*	2"x20'	03950	2220'	2.375	.154	280 PSI	69.5	
PVC 4025‡	2½"x20'	04205	1460'	2.875	.203	300 PSI	110.0	
PVC 7300*	3"x10'	03951	1130'	3.500	.216	260 PSI	144.2	
PVC 7300*	3"x20'	03952	1000'	3.500	.216	260 PSI	144.2	
PVC 7400†	4"x10'	03953	670'	4.500	.237	220 PSI	205.5	
PVC 7400†	4"x20'	03954	1340'	4.500	.237	220 PSI	205.5	
PVC 7500†	5"x20'	04837	760'	5.563	.258	190 PSI	272.5	
PVC 7600†	6"x10'	03955	330'	6.625	.280	180 PSI	361.2	
PVC 7600†	6"x20'	03956	660'	6.625	.280	180 PSI	361.2	
PVC 7800†	8"x10'	13087	140'	8.625	.322	160 PSI	543.6	
PVC 7800†	8"x20'	03958	280'	8.625	.322	160 PSI	543.6	
PVC 7910†	10"x20'	03959	220'	10.750	.365	140 PSI	770.7	
PVC 7912†	12"x20'	03961	120'	12.750	.406	130 PSI	1019.0	
PVC 7914†	14"x20'	04862	60'	14.000	.437	130 PSI	1205.0	
PVC 7916†	16"x20'	04918	60'	16.000	.500	130 PSI	1575.7	

\* Dual marked ASTM D 1785 and ASTM D 2665.

† Triple Marked ASTM D 1785 & ASTM D 2665 & ASTM F 480.

‡ Dual marked ASTM D 1785 and ASTM F 480.

NSF Listed. Meets All Requirements of ASTM D 1784 and ASTM D 1785.

All products manufactured by Charlotte Pipe and Foundry Company are proudly made in the U.S.A.



**You can't beat the system.®**

**WARNING**

Testing with or use of compressed air or gas in ABS / CPVC / PVC / Cast Iron pipe or fittings can result in explosive failures and cause severe injury or death.

AIR/GAS

- NEVER test with or transport/store compressed air or gas in ABS / CPVC / PVC / Cast Iron pipe or fittings.
- NEVER test ABS / CPVC / PVC / Cast Iron pipe or fittings with compressed air or gas, or air over water boosters.
- ONLY use ABS / CPVC / PVC / Cast Iron pipe or fittings for water or approved chemicals.
- Refer to warnings on PPA's website and ASTM D 1785.

## TERMS AND CONDITIONS OF SALE

Terms and Conditions of Sale can be found at [https://charlottepipe.com/terms\\_and\\_conditions.aspx](https://charlottepipe.com/terms_and_conditions.aspx)

### LIMITED WARRANTY

Charlotte Pipe and Foundry Company® (Charlotte Pipe®) Products are warranted to be free from manufacturing defects and to conform to currently applicable ASTM standards for a period of five (5) years from date of delivery. Buyer's remedy for breach of this warranty is limited to replacement of, or credit for, the defective product. This warranty excludes any expense for removal or reinstallation of any product and any other incidental, consequential, or punitive damages. **This limited warranty is the only warranty made by seller and is expressly in lieu of all other warranties, express and implied, including any warranties of merchantability and fitness for a particular purpose.** No statement, conduct or description by Charlotte Pipe or its representative, in addition to or beyond this Limited Warranty, shall constitute a warranty. This Limited Warranty may only be modified in writing signed by an officer of Charlotte Pipe.

This Limited Warranty will not apply if:

- 1) The Products are used for purposes other than their intended purpose as defined by local plumbing and building codes, and the applicable ASTM standard.
- 2) The Products are not installed in good and workmanlike manner consistent with normal industry standards; installed in compliance with the latest instructions published by Charlotte Pipe and good plumbing practices; and installed in conformance with all applicable plumbing, fire and building code requirements.
- 3) This limited warranty does not apply when the products of Charlotte Pipe are used with the products of other manufacturers that do not meet the applicable ASTM or CISPI standards or that are not marked in a manner to indicate the entity that manufactured them.
- 4) In hubless cast iron installations, this warranty will not apply if products are joined with unshielded hubless couplings. Charlotte Pipe requires that its hubless cast iron pipe and fittings be joined only with shielded hubless couplings manufactured in accordance with CISPI 310, ASTM C 1277 and certified by NSF® International or with Heavy Duty Couplings meeting ASTM C 1540.
- 5) The Products fail due to defects or deficiencies in design, engineering, or installation of the piping system of which they are a part.
- 6) The Products have been the subject of modification; misuse; misapplication; improper maintenance or repair; damage caused by the fault or negligence of anyone other than Charlotte Pipe; or any other act or event beyond the control of Charlotte Pipe.
- 7) The Products fail due to the freezing of water in the Products.
- 8) The Products fail due to contact with chemical agents, fire stopping materials, thread sealant, plasticized vinyl products, or other aggressive chemical agents that are not compatible.
- 9) Pipe outlets, sound attenuation systems or other devices are permanently attached to the surface of Charlotte® PVC, ABS or CPVC products with solvent cement or adhesive glue.

Charlotte Pipe products are manufactured to the applicable ASTM or CISPI standard. Charlotte Pipe and Foundry **cannot** accept responsibility for the performance, dimensional accuracy, or compatibility of pipe, fittings, gaskets, or couplings not manufactured or sold by Charlotte Pipe and Foundry.

This Limited Warranty will not apply unless written notice of a claim is mailed to Charlotte Pipe at the address below within 30 days of discovery of the allegedly defective product.

Any Charlotte Pipe products alleged to be defective **must** be made available to Charlotte Pipe at the following address for verification, inspection and determination of cause:

Charlotte Pipe and Foundry Company  
Attention: Technical Services  
2109 Randolph Road  
Charlotte, North Carolina 28207

**Purchaser must obtain a return materials authorization** and instructions for return shipment to Charlotte Pipe of any product claimed defective or shipped in error.

Any Charlotte Pipe product **proved** to be defective in manufacture will be replaced F.O.B. point of original delivery, or credit will be issued, at the discretion of Charlotte Pipe.

5/19/23

Charlotte, Charlotte Pipe and "You can't beat the system" are registered trademarks of Charlotte Pipe and Foundry Company.